

The background of the entire page is a light gray, stylized circuit board pattern. It features a complex network of lines representing traces and various circular shapes representing components or vias, all set against a white background.

BUF 3 2 3 0

**3 Port USB 2.0 HUB
3 Port 1394 Repeater**

Hardware Guide

DESCRIPTION:

The BUF3230 is 3 Port 1394 REPEATER, USB2.0 3 PORT HUB

Check your packing listing:

BUF3230 x 1
Hardware Guide x 1

**** If any of these items are missing from the BUF3230 Retail package, contact your supplier immediately.**

Hardware Specification

1394 3 PORT REPEATER, 400 Mbps speed support.
USB 2.0 3PORT HUB, 480 Mbps speed support.

TECHNICAL SPECIFICATION:

Compatibility: -1394 Version A
-USB 2.0/1.1


Operating system: -WIN 98/SE, ME, 2000, XP

Chips: -FW803
-UPD720110.

Connections:
Connector Type -USB CONNECTOR x 3
-1394 CONNECTOR x 3

Attaching to 5.25 inch Bay :

1. Make sure your computer is powered off. Then attach the BUF3230 to 5.25 inch bay. Attach cable for adapter connection to the front-bay extension adapter, as shown below.



Power cable for
adapter connection


2. Insert the BFW3230 into 5.25 inch bay and fix it, as shown below.



3. Connect the USB cable to the PCI USB adapter.



4. Connect the 1394 cable to the PCI 1394 adapter.



5. Install the USB adapter or 1394 adapter into the PCI slot. Press down firmly until the card clicks into place. Then, screw down the bracket of the USB adapter or 1394 adapter, as shown below.



6. Then finished.